



solis

20<sup>th</sup>  
ANNIVERSARY



NEW



## Grid-Tied Inverters

# S6-GC3P(150-200)K07-ND

7 MPPT | 54A per MPPT



### Safety, Intelligent Prevention

- Integrated meteorological equipment, intelligent system inefficiency warning
- AI-based millisecond arc protection (AFCI)
- Real time PV grounding detection and protection
- Arc fault and RSD (Rapid Shutdown) co-operation for improved fire safety (optional)
- Intelligent AC and DC terminal temperature sensing detection



### Innovation, Never Stops

- Master-slave export power control solution, flexible and fast control, support 10 units in parallel
- Dual independent RS485 ports, perfect adaptation to third-party integration
- Supports single and multiple genset applications without the need for an external genset controller
- The industry's first master-slave export power control+ three-phase unbalanced output control, allocate each phase power on demand, and flexibly compatible with various power grids (optional)

GINLONG TECHNOLOGIES CO., LTD.

t: +86 574 6580 2188 e: sales@ginlong.com  
w: solisinverters.com service@ginlong.com



# DATASHEET

# S6-GC3P(150-200)K07-ND

Models	150K07-NV	200K07-HV
<b>Input DC</b>		
Max. input voltage	1100 V	
Rated voltage	600 V	720 V
Start-up voltage	180 V	
MPPT voltage range	160 - 1000 V	
Max. input current	7 × 54 A	
Max. short circuit current	7 × 75 A	
MPPT number / Max. input strings number	7 / 21	
<b>Output AC</b>		
Rated output power	150 kW	200 kW@35°C
Max. apparent output power	165 kVA	220 kVA
Max. output power	165 kW	220 kW
Rated grid voltage	3/N/PE, 220 V / 380 V, 230 V / 400 V	3/PE, 480 V
Rated grid frequency	50 Hz / 60 Hz	
Rated grid output current	216.5 A / 227.9 A	240.6 A
Max. output current	250.6 A	240.6 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)	
THDi	< 3%	
DC injection current	0.5%In	
<b>Efficiency</b>		
Max. efficiency	98.8%	
EU efficiency	98.3%	
<b>Protection</b>		
DC reverse-polarity protection	Yes	
Short circuit protection	Yes	
Output over current protection	Yes	
Insulation resistance monitoring	Yes	
Residual current detection	Yes	
Surge protection	DC Type II / AC Type II	
Grid monitoring	Yes	
Anti-islanding protection	Yes	
Temperature protection	Yes	
Strings monitoring	Yes	
Night SVG function	Yes	
I/V Curve scanning	Yes	
Integrated AFCI 2.0	Optional	
Integrated PID recovery	Optional	
Integrated DC switch	Yes	
<b>General Data</b>		
Dimensions (W × H × D)	1035.5 × 869 × 396 mm	
Weight	105 kg	
Topology	Transformerless	
Self-consumption (night)	< 2 W	
Operating ambient temperature range	- 30 ~ +60°C	
Relative humidity	0 - 100%	
Ingress protection	IP66	
Noise emission (typical)	≤ 80 dB(A)	
Cooling concept	Intelligent fan-cooling	
Max. operation altitude	4000 m	
Grid connection standard	G99, IEC61727, EN50549-1/2, VDE4110	
Safety / EMC standard	IEC/EN 62109-1/-2, IEC60947-2, IEC/EN 61000-6-2/-4	
<b>Features</b>		
DC connection	MC4 connector	
AC connection	OT terminal (max. 400 mm <sup>2</sup> )	
Display	LED indicator & Bluetooth + APP	
Communication	RS485, Optional: S3-WiFi-ST, S3-GRPS-ST, PLC	